



3949S™ LOW VOC CLEANER



GENERAL

DESCRIPTION

A 0.4 lb/gal (49 g/l) category compliant lacquer and enamel cleaner designed for removing sanding sludge, dust, fingerprints, small amounts of grease and oil prior to painting.

The products referenced herein may not be sold in your market. Please consult your distributor for product availability.



MIXING

COMPONENTS

3949S™ Low VOC Cleaner

MIX RATIO

Ready to use.

Tips for Success

Shake well before using



APPLICATION

SUBSTRATES

- Sanded and unsanded substrates
- OEM finishes
- Repainted surfaces
- Cured sealers

SURFACE PREPARATION

Clean surface with mild detergent and water.

APPLICATION

- Soak clean cloth with 3949S™ Low VOC Cleaner.
- Wipe surface to loosen and lift the contaminants. Follow immediately by wiping thoroughly with a clean dry cloth.

Tips for Success

- Do not allow 3949S™ Low VOC Cleaner to dry on the surface. If this does occur, simply re-wet and wipe dry.
- Use a spray bottle for easy application, and use a clean cloth for wiping and applying 3949S™ Low VOC Cleaner.



PHYSICAL PROPERTIES

All Values Ready To Spray

Max. VOC (AP):	49 g/L (.4 lbs./gal)
Avg. Gal. Wt.:	989 g/L (8.25 lbs./gal)
Avg. Wt.% Volatiles:	100.0%
Avg. Wt.% Exempt Solvent:	0.0%
Avg. Wt.% Water:	94.9%
Avg. Vol.% Exempt Solvent:	0.0%
Avg. Vol.% Water:	94.1%
Flash Point:	See SDS



VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and MSDS/SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: October 2017

In the United States:
1.855.6.AXALTA
cromax.us

In Canada:
1.800.668.6945
cromax.ca

