

# Low VOC Chart

For Sacramento Metro AQMD Rule 459

Automotive, Mobile Equipment, and Associated Parts and Components Coating Operations

Effective: February 25, 2012

Revised: January 2024

## Compliant Aerosol Coating Products | County Rules Exemption

CODE	DESCRIPTION	CODE	DESCRIPTION
402-01™	Gloss Trim Black	421-24™	Gray Primer
402-02™	Flat Trim Black	421-25™	Red Oxide Primer
402-03™	Semi Gloss Trim Black	421-26™	Beige Primer
403-00™	Clearcoat	492-51™	Undercoating

## Cleaning Solvents | 25 g/L (0.21 lb./gal)

CODE	DESCRIPTION	REMARKS	APPLIED VOC
107™	Gun & Equipment Cleaner		25 g/L
130™	Cleaner		0 g/L
220™	Silicone Remover Low VOC	¥ See footer	25 g/L
225™	Bug & Tar Remover	¥ See footer	347 g/L
139™	Bug & Tar Remover	¥ See footer	347 g/L
VS1100™	Surface Cleaning Solvent		0 g/L

## Pretreatment Coating VOC Limit | 660 g/L (5.5 lb./gal)

CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
VS3000™	Etch Primer	2:1	VS3001™	-	647 g/L

## Adhesion Promoter VOC Limit | 540 g/L (4.5 lb./gal)

CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
VS2000™	Plastic Adhesion Promoter	-	-	-	539 g/L

## Primer VOC Limit | 250 g/L (2.1 lb./gal)

CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
421-1X	Primer (⌘ - Note in footer)	4:1	483-03™	-	250 g/L
421-30™	Primer Surfacer	1:1	-	441-60™	250 g/L

## Primer Sealer VOC Limit | 250 g/L (2.1 lb./gal)

CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
421-1X	Sealer (⌘ - Note in footer)	3:1:2	483-03™	401-X5	250 g/L
491-1X	Primer Sealer	2:1	483-01™ / 483-02™	-	250 g/L

## Single Stage Coating VOC Limit | 340 g/L (2.8 lb./gal)

Additional additives may be used. Consult technical data sheet for usage and compliance.

CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
NIS	Ful-Thane® 2K Low VOC Single Stage Topcoat	4:1:1	VS5330	VS515#	340 g/L
412-105	Ful-Thane® Low VOC Fac Pac Black NIS	4:1:1	VS5330	VS515#	340 g/L
412-106	Ful-Thane® Low VOC Fac Pac White NIS	4:1:1	VS5330	VS515#	340 g/L

## Color Coating VOC Limit | 420 g/L (3.5 lb./gal)

Additional additives may be used. Consult technical data sheet for usage and compliance.

CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
IR	Ful-Base® Basecoat	1:1	‡ See Footer	441-6X	420 g/L

## Clear Coating VOC Limit | 250 g/L (2.1 lb./gal)

CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER	MAX APPLIED VOC (LE)*
462-00™	Clearcoat	4:1	483-84™ / 483-85™	-	250 g/L
468-00™	Clearcoat	4:1	483-84™ / 483-85™	-	250 g/L
468-00™	Clearcoat	3:1	483-86™	-	250 g/L
476-00™	Clearcoat	2:1	483-64™ / 483-65™	-	250 g/L

Other components that may be used (list is not all-inclusive). Consult technical data sheet for usage and compliance.

CODE	DESCRIPTION	MIX RATIO	HARDENER	REDUCER
VS4510	Axalta® 2K Urethane Low VOC Integrated Clear	4:1:1	VS5330	VS515#
VS6550	Axalta® Accelerator			
VS6500	Axalta® Fisheye Eliminator			
VS6200	Axalta® VS6200 Matte Base Additive			
441-83™	Low VOC Flow Additive			

⌘ - Refers only to products 421-10™, 421-11™ & 421-12™

⌘ Rule 459 section 310.7 (CCR Section 94507)

‡ Optional Activation: Add 1 oz. 483-56™ RTS quart

**\*Less Water, Less Exempt**

# = 6, 7, 8, 9

X = 0, 1, 2, 6, 8